

Workshop on Product Intelligence (Concepts and Theory)

Theodor Borangiu, Silviu Raileanu

University Politehnica of Bucharest, Department of Automation & Applied Informatics


CIMR Centre, cimr@cimr.pub.ro , www.cimr.pub.ro

Cambridge, September 24-25, 2012

Supporting holonic control architecture for IP

Model composition:

1. **Staff Holon** : global production planning, scheduling, coordinator, GUI and production strategy decider;
2. **Order Holon**: an aggregate intelligent entity in charge of taking real-time decisions;
3. **Resource Holon**: physical resources together with the control counterpart;
4. **Product and Process Knowledge Database (PPKB)**: stores the operations structure for the products;
5. **Resource Service Access Model (RSAM)**: distributed autonomous entity in charge of collecting resource information and offering it in a concise manner.




IP model

- *Embedded intelligence*, handles:



- ✓ the updated model of resource services access (RSAM);
- ✓ the product model;
- ✓ an inter-agent communication protocol;
- ✓ a set of resource allocation algorithms (real-time scheduling);
- ✓ product-driven automation (in dMES):
 - “Next-operation” scheduling (schedule progressively created);
 - “Packet optimization” scheduling (complete schedule first computed)

- ✓ *Location* of intelligence – evolution
- ✓ *Complexity* of product & production data – operations, precedence, technology, tooling





Product-driven automation in heterarchical manufacturing control

- Dynamics of the control model: allocation process & Mediator
- Process objective:
 - Makespan minimization and equal resource utilization
 - Adaptability to perturbations
- Real-time decentralized resource allocation




IP - Digital representation of product [processing sequence]





IP - Digital representation of product [tooling]

Robot-driven shape reconstruction for 4-dim. machining

Compute 3D Tool Compensation from Image Processing




Part surface (depth map)



Milling Tool Shape (depth map)



Morphological dilation





Milling Surface

The surface where the tip of the cutting tool can move in order to be always tangent to the part surface



Tool Shape Modelling



Conic Mill



Round End Mill



Bull End Mill